

Product Datasheet		Catalog Home Home Page Search	
<h2>HBL2621 -- Twist-Lock Plug</h2>			
		2P3W, 30A 250V, L6-30P, Black & White Nylon HBL2621	
Product Specifications			
Product Type	 Twist-Lock Devices		
Product Item	Plug		
Wiring Scheme	2-Pole, 3-Wire Grounding		
Amperage	30A		
Voltage	250V AC		
NEMA Configuration	L6-30P		
Item Style	Insulgrip		
Device Color	Black/White		
Horsepower	2		
Cord Dia.	.360"-.930" (9-24)		
Blade Holder Material	Natural White Nylon		
Terminal Retainer Material	Clear polycarbonate		
Housing Material	Black nylon		
Cord Clamp Material	Natural (white) nylon		
Blade Material	Brass		
Terminal Clamp Material	.08" (2)steel-nickel plated		
Terminal Screw Material	#10-32 Brass (white finish on neutral screw when used) Multi-drive		
Ground Screw Material	#10-32 Brass (green finish) Multi-drive		
Cord Clamp Screw Material	Steel, zinc plated Multi-drive		
Body Holding Screw Material	Steel, zinc plated Multi-drive		
Ratings	Molded In or Stamped On		
Catalog No	Permanently ink marked on product		
Dielectric Voltage Withstand	2,000V minimum		
Current Interrupting	Certified for current interrupting at full rated current		
Temperature Rise	Max 30C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of .75.		
Cord Accommodation	Round portable service cords of diameters commensurate with the device rating as defined in UL Standard 62, CSA C22.2 No. 49.		
Terminal Accommodation	30A #10 AWG		
Terminal Identification	Terminals identified in accordance with UL 498 (X, Y, Z, White, Green)		
Flammability	HB or better per UL 94 or CSA 22.2 No. 0.6		
Operating Temperatures	Maximum Continuous 75 C Minimum -40 C (w/o impact)		
Moisture Resistance	IP20		
Listings	FED SPEC UL/CSA		
UPC Number	783585038834		
Weight in LBs	0.25		
Link to Drawing Library	Click here for Library		
Link to PDF Catalog	Click here for Catalog		

