



SANblade®

2-Gbps Fibre Channel (FC) to
PCI-X Host Bus Adapters (HBAs)

QLA® 2340/
QLA2340L



Ease of Use

- Autonegotiation of Fibre Channel speed bit rate (1 Gbps or 2 Gbps)
- Easy detection of activities through an LED panel:
 - Power
 - Online
 - Signal acquired
 - Loss of synchronization
 - Firmware error
- Automatic topology detection
- Quick start guide
- Persistent binding

Superior Scalability

- Concurrent support for SCSI and IP protocols
- Load balancing for optimized performance
- Simultaneous initiator and target mode support
- Local and remote management

Enhanced Reliability

- Unique, single-integrated Fibre Channel controller for added reliability and optimum performance

• HBA and LUN level failover

• LUN masking

• Loopback and read/write buffer tests

Why QLOGIC? Designed and deployed by major server and storage OEMs, the QLogic SANblade QLA2340 and QLA2340L host bus adapters (HBAs) offer the ultimate in performance: 2-Gbps Fibre Channel combined with 64-bit, 133-MHz PCI-X. Eliminating traditional host bottlenecks that impede the high performance of 2-Gbps Fibre Channel, this union of the fastest I/O and host technologies creates the perfect balanced solution.

These HBAs are based on unique single chip fibre channel controller architecture from QLogic. These multimode optic HBAs are specifically designed for servers in direct attach storage (DAS) as well as storage area network (SAN) environments.

Cost Effective. The QLA2340 is the right solution for the added boost in performance. If you are looking for low-profile boards for 1U and 2U servers, the QLA2340L, a low-profile version of the QLA2340, is the perfect fit.

Leading Single Chip Integration. The QLA2340/2340L uniquely integrates a RISC processor, a Fibre protocol engine, and transceivers into a single, efficient FC controller chip that increases reliability and performance by lowering CPU utilization.

Broad OEM Acceptance. The QLA2340/2340L HBA is validated by every major OEM including Dell, EMC, HDS, HP, IBM, and Sun. The QLA2340's extensive certification from major server and storage manufacturers makes it the perfect choice for multiplatform requirements.

Simplified Setup. Point-and-click installation and configuration wizards simplify the HBA setup process. Storage administrators can quickly deploy HBAs across a SAN using standard HBA management tools and device utilities. The QLA2340/40L is also fully compatible with industry standard application programming interfaces (APIs), including SNIA HBA API and SMI-S, thereby allowing administrators to manage QLogic HBAs using third-party software applications.

Proven Architecture. The QLA2340/2340L architecture is the result of more than 15 years of progressive development and testing. Proven architecture from QLogic delivers higher overall reliability and enables advanced functionality with its single-chip integration, placing QLogic years ahead of its competitors. The QLA2340/2340L also has proven interoperability with all major software applications, hardware platforms, and operating systems.

The Bottom Line. Driving the standard for interoperability with extensive FC testing in SAN environments, you can feel confident in choosing the QLogic solution.



Host Bus Interface Specifications

Speed	64-bit, 133-MHz PCI-X
Signal voltage	3.3 V and 5.0 V buses supported
Compliance	PCI Local Bus Specification rev. 2.2, PCI-X Addendum rev. 1.0a, PCI Hot Plug Specification rev. 1.0, PCI Bus Power Management Interface Specification rev 1.1

Fibre Channel Specifications

Speed	200 MBps maximum at half-duplex, 400 MBps maximum at full-duplex
Topology	FC-AL, FC-AL-2, point to point, switched fabric (FL_Port and F_Port)
Buffer credits	For 512-byte frame size, 9 credits issued. For 2K-byte frame size, 3 credits issued.
Class of service	Class 3 Fibre Channel service
Protocols	SCSI-FCP, IP, FC-TAPE
Compliance	Second Generation FC Generic Services Definition (FC-GS-2), Third Generation FC Generic Services Definition (FC-GS-3), Fibre Channel-Physical and Signaling Interface (FC-PH), SCSI-3 Fibre Channel Protocol (SCSI-FCP), Fibre Channel-Arbitrated Loop-2 (FC-AL-2), Fibre Channel-Private Loop Direct Attach Technical Report (FC-PLDA), RFC 2625 IP and APR Over Fibre Channel, Fibre Channel Framing and Signaling (FC-FS)

Physical Specifications

Ports	One
Media	Multimode optic
Optics	Short wave laser
Connectors	LC-style connector that supports non-OFC, multimode fibre optic cabling using a small form factor optical transceiver module
Form factor	Low-profile MD2: 16.93 cm×5.15 cm (6.7"×2.5")
Bracket size	QLA2340: standard size; QLA2340L: low-profile size

Environment and Equipment Specifications

Temperature	Operating: 0°C/32°F to 55°C/131°F. Storage: -20°C/-4°F to 70°C/158°F	
Airflow	0 lf/m	
Humidity	Relative (noncondensing): 10% to 90%, Storage: 5% to 95%	
Power dissipation	~ 7.0 watts	
Cable	50/125µm multimode fiber, 62.5/125 µm multimode fiber	
Cable distances	1 Gbps: 500 meters 50/125 µm fiber, 300 meters 62.5/125 µm fiber	2 Gbps: 300 meters 50/125 µm fiber, 150 meters 62.5/125 µm fiber

Agency Approvals—Product Safety

US/Canada	UL, cUL UL60950 CSA C22.2 No.60950 Class 1 Laser Product per DHHS 21CFR J
Europe	73/23/ECC Low Voltage Directive: TUV: EN60950: 1992+A1,2,3,4,11 EN60825-1: 1994+A11 EN60825-2: 1994

Agency Approvals—EMI and EMC

US	FCC Part 15, Class B
Canada	Industry Canada ICES-003, Class B
Europe	89/336/EEC EMC Directive CE Mark: EN55022: 1998 /CISPR22:1997 Class B EN55024: 1998 EN61000-3-2:1995 EN61000-3-3:1994
Japan	VCCI, Class B
Taiwan	CNS 13438 Class B
New Zealand/Australia	AS/NZS 3548 Class B
Korea	MIC

Tools and Utilities

Management tools	FC HBA Manager
Device utilities	Command line interface; configuration utilities resident with BIOS and FCode
Boot support	Intel x86: BIOS (32-bit), EFI (64-bit); Solaris SPARC: FCode
APIs	SNIA HBA API V2, SMI-S, and FDMI
Operating systems	Windows Server 2003 (32-bit and 64-bit), Windows NT, Windows 2000, Solaris SPARC, Linux (32-bit and 64-bit), Novell NetWare, Mac OS X

Ordering Information

QLA2340	Ships to OEMs in an individually packed box with a standard size bracket
QLA2340-CK	Ships in an individually packed box with a standard size bracket, spare low-profile bracket, FC HBA Manager, and Quick Start Guide
QLA2340-BK	Ships in a bulk box in quantities of 20 or 50 with standard size brackets
QLA2340L	Ships to OEMs in an individually packed box with a low-profile size bracket
QLA2340L-CK	Ships in an individually packed box with a low-profile bracket, spare standard size bracket, FC HBA Manager, and Quick Start Guide
QLA2340L-BK	Ships in a bulk box in quantities of 20 or 50 with low-profile brackets



QLogic Corporation
26650 Aliso Viejo Parkway
Aliso Viejo, CA
92656
949.389.6000

QLogic (UK) Ltd.
Surrey Technology Centre
40 Occam Road, Guilford
Surrey GU2 7YG UK
+44 (0) 1483 295825

WWW.QLOGIC.COM

© 2003–2006 QLogic Corporation. Specifications are subject to change without notice. All rights reserved worldwide. QLogic, the QLogic logo, QLA, and SANblade are registered trademarks of QLogic Corporation. SANtrack is a trademark of QLogic Corporation, which may be registered in some jurisdictions. All other brand and product names are trademarks or registered trademarks of their respective owners. Information supplied by QLogic Corporation is believed to be accurate and reliable. QLogic Corporation assumes no responsibility for any errors in this brochure. QLogic Corporation reserves the right, without notice, to make changes in product design or specifications.