

## NOTES:

- 1. ALL DIMENSIONS ARE IN MILLIMETERS AND INCHES
- 2. GLASS THICKNESS: 3.0mm/.12" NOMINAL.
- 3 TRANSDUCERS ARE LOCATED AT THE POSITIONS SHOWN.
  HEIGHT OF TRANSDUCERS ABOVE GLASS: 3.0mm[0.12"] MAX.
- 4. NO MATERIAL EXTENDS MORE THAN 0.8mm/.03 BEYOND THE BACK SURFACE OF THE GLASS.
- (ALONG THE EDGE) OF THE GLASS.
- BERG 65043-031, 2x6 HOUSING WITH BERG 48239-000 RECEPTACLES, DIRECTLY MATES WITH ANY OF THE FOLLOWING:
  -INTELLITOUCH SERIAL CONTROL BOARD
  -012226 CABLE (2x6 TO 8" DB9 BULKHEAD)
- 7. THE TOUCH ACTIVE AREA IS LESS THAN THE VIEWABLE AREA TO FACILITATE SEALING.

BLK	WHT	X RECEIVE (+)	11
RED	GRN	X TRANSMIT (+)	10
BLK	RED	X RECEIVE (-)	9
RED	RED	X TRANSMIT (-)	∞
	INNER SHIELD	GROUND	7
GRY	YEL	Y TRANSMIT (-)	6
BLK	BLK	Y RECEIVE (-)	5
GRY	BLU	Y TRANSMIT (+)	4
BLK	BLU	Y RECEIVE (+)	3
		KEY	2
	OVERALL SHIELD	GROUND	_
JACKET COLOR	INSULATION COLOR JACKET COLOR	SIGNAL	N
	CONNECTION CHART	CONNI	
			I

