

# Data Sheet

## FUJITSU Server PRIMERGY TX120 S3p Tower Server

For small environments with high demands

FUJITSU Server PRIMERGY systems provide the most powerful and flexible data center solutions for companies of all sizes, across all industries and for any type of workload. This includes expandable PRIMERGY tower servers for remote and branch offices, versatile rack-mount servers, compact and scalable blade systems, as well as density-optimized scale-out servers. They convince by business proven quality with a wide range of innovations, highest efficiency cutting operational cost and complexity, and provide more agility in daily operations in order to turn IT faster into a business advantage.

Perfect for small and medium businesses as well as branch offices, FUJITSU Server PRIMERGY TX tower systems are robust and cost-efficient servers by providing rock solid reliability. Additionally they are characterized by simple IT operations, low power consumption and quiet operation so that they can be handled by non-technically trained staff and can be used in standard office environments. By the way: Almost all PRIMERGY TX servers can be rack-mounted to offer best flexibility.

### PRIMERGY TX120 S3p

Fujitsu Server PRIMERGY TX120 S3p: For small environments with high demands. It is the perfect server for environments where space, high server functionality and low TCO are crucial. The TX120 S3p is an excellent choice for smaller retail premises, branch offices, or in other contexts where strict legal controls apply, e.g. medical, legal or financial services. Besides sporting a power supply with 94% efficiency and 0-watt functionality, the TX120 S3p keeps running costs and the environmental impacts low. The unique combination of ultra-compact form factor, Intel® Xeon® processor E3 series performance, high availability features and low TCO, make it ideal for demanding environments where space is scarce.



# Features & Benefits

Main Features	Benefits
<ul style="list-style-type: none"><li>■ Its ultra-compact form factor, means that the PRIMERGY TX120 S3p fits everywhere, in either tower or desktop position</li><li>■ 2x 1Gigabit LAN as standard and optional 2.5-inch hot-plug hard disks</li><li>■ The Intel® Xeon® processor E3 family-based platform and the highly efficient power supply unit with 0-Watt functionality</li><li>■ The onboard remote management controller (iRMC S3), and the optional front service LAN, makes it easier to service your TX120 S3p</li><li>■ Available with two different base units with either up to 2x 3.5-inch hard disks or up to 4x 2.5-inch hard disks</li><li>■ Halogen-free printed circuit board</li></ul>	<ul style="list-style-type: none"><li>■ Space-saving: ideal for office, retail and smaller environments</li><li>■ High-availability to keep your business processes going</li><li>■ High performance and energy efficiency</li><li>■ High manageability and serviceability - saving you time</li><li>■ Flexibly adapts to your storage needs</li><li>■ For environmentally friendly waste disposal</li></ul>

# Technical details

## PRIMERGY TX120 S3p

Base unit	PRIMERGY TX120 S3	PRIMERGY TX120 S3p LFF
Housing types	Ultra-compact form-factor	Ultra-compact form-factor
Storage drive architecture	4x 2.5-inch SAS/SATA	2x 3.5-inch SATA (non hot-plug)

## Mainboard

Mainboard type	D3049
Chipset	Intel® C202
Processor quantity and type	1 x Intel® Celeron® processor / Intel® Pentium® processor / Intel® Core™ i3 processor / Intel® Xeon® processor E3-1200v2 product family

Processor	Intel® Celeron® processor G1610 (2C/2T, 2.60 GHz, TLC: 2 MB, Turbo: No, 1,333 MHz, 55 W)
	Intel® Core™ i3-3220 processor (2C/4T, 3.30 GHz, TLC: 3 MB, Turbo: No, 1,600 MHz, 55 W)
	Intel® Pentium® processor G2120 (2C/2T, 3.10 GHz, TLC: 3 MB, Turbo: No, 1,600 MHz, 55 W)
	Intel® Xeon® processor E3-1220Lv2 (2C/4T, 2.30 GHz, TLC: 3 MB, Turbo: Yes, 1,600 MHz, 17 W)
	Intel® Xeon® processor E3-1220v2 (4C/4T, 3.10 GHz, TLC: 8 MB, Turbo: Yes, 1,600 MHz, 69 W)
	Intel® Xeon® processor E3-1230v2 (4C/8T, 3.30 GHz, TLC: 8 MB, Turbo: Yes, 1,600 MHz, 69 W)
	Intel® Xeon® processor E3-1240v2 (4C/8T, 3.40 GHz, TLC: 8 MB, Turbo: Yes, 1,600 MHz, 69 W)
	Intel® Xeon® processor E3-1265Lv2 (4C/8T, 2.50 GHz, TLC: 8 MB, Turbo: Yes, 1,600 MHz, 45 W)

Memory slots	4
Memory slot type	DIMM (DDR3) UDIMM
Memory capacity (min. - max.)	2 GB - 32 GB
Memory protection	ECC
Memory notes	Mix and match possible; with dual channel operation better performance (2 modules with equal capacity necessary). Single channel (1 module) configuration possible.

Memory options	4 GB (1 module(s) 4 GB) DDR3, unbuffered, ECC, 1,600 MHz, PC3-12800, DIMM, dual rank 8 GB (1 module(s) 8 GB) DDR3, unbuffered, ECC, 1,600 MHz, PC3-12800, DIMM, dual rank
----------------	--

## Interfaces

USB 2.0 ports	10 x USB 2.0 (2x front, 6x rear, 2x internal; the 2 internal ports cannot be used in parallel)
Graphics (15-pin)	1 x VGA
Serial 1 (9-pin)	1 x RS-232-C
LAN / Ethernet	2
Management LAN (RJ45)	1 x dedicated management LAN port for iRMC S3 (10/100/1000 Mbit/s) Optional front Service LAN port (10/100 Mbit/s)

## Onboard or integrated Controller

RAID controller	4 port SATA with RAID 0/1/10 for HDDs
SATA Controller	Intel® C200
SATA controller type notes	4 port for internal SATA HDDs with RAID 0, 1, 10 for Windows and Linux
LAN Controller	Intel® 82574L + Intel® 82579LM onboard, 2 x 10/100/1000 Mbit/s Ethernet (TCP/IP acceleration), iSCSI and PXE-Boot via LAN, WoL for Intel® 82574L only.
Remote management controller	Integrated Remote Management Controller (iRMC S3, 32 MB attached memory incl. graphics controller) IPMI 2.0 compatible
Trusted Platform Module (TPM)	optional TPM

<b>Slots</b>	
PCI-Express 3.0 x16	1 x Low profile
PCI-Express 2.0 x1 (mech. x4)	1 x Low profile
PCI-Express 2.0 x4 (mech. x8)	1 x Low profile (In SAS configuration 1x PCI-Express slot occupied by modular RAID controller.)
PCI-slots	1 x Low profile (PCI 32-bit / 33 MHz, 5 V)
Slot Notes	In configurations with Intel® Core™ i3 or Intel® Pentium® processors slots are operated with PCI-Express 2.0.

<b>Drive bays</b>	
Storage drive bays	4 x 2.5-inch hot-plug SAS/SATA or 2x 3.5-inch non hot-plug SATA.
Storage drive bay configuration	Not upgradeable in the field.
Accessible drive bays	1 x 3.5/1.6-inch for backup devices 1 x 5.25/0.5-inch for CD-RW/DVD
Optional hard disk bays	None
Number of fans	3
Fan notes	Processor fan, rear fan, drive fan

<b>Operating panel</b>	
Operating buttons	On/off switch
Status LEDs	Power (amber / green)

### Operating Systems and Virtualization Software

<b>Certified or supported operating systems and virtualization software</b>	Microsoft® Hyper-V Server 2012 R2
	Microsoft® Windows Server® 2012 R2 Datacenter
	Microsoft® Windows Server® 2012 R2 Standard
	Microsoft® Windows Server® 2012 R2 Essentials
	Microsoft® Windows Server® 2012 R2 Foundation
	Microsoft® Windows Storage Server 2012 R2 Standard
	Microsoft® Hyper-V Server 2012
	Microsoft® Windows Server® 2012 Datacenter
	Microsoft® Windows Server® 2012 Standard
	Microsoft® Windows Server® 2012 Essentials
	Microsoft® Windows Server® 2012 Foundation
	Microsoft® Windows Storage Server 2012 Standard
	Microsoft® Hyper-V™ Server 2008 R2
	Microsoft® Windows Server® 2008 R2 Datacenter
	Microsoft® Windows Server® 2008 R2 Enterprise
	Microsoft® Windows Server® 2008 R2 Standard
	Microsoft® Windows Server® 2008 R2 Foundation
	Microsoft® Windows® Web Server 2008 R2
	Microsoft® Windows® Small Business Server 2011 Premium Add-On
	Microsoft® Windows® Small Business Server Standard 2011
	Microsoft® Windows® Server 2008 Datacenter
	Microsoft® Windows® Server 2008 Enterprise
	Microsoft® Windows® Server 2008 Standard
	Microsoft® Windows® Web Server 2008
	SUSE® Linux Enterprise Server 11
	SUSE® Linux Enterprise Server 10
	Red Hat® Enterprise Linux 7
Red Hat® Enterprise Linux 6	
Red Hat® Enterprise Linux 5	
Oracle® VM 3	
<b>Operating system release link</b>	<a href="http://docs.ts.fujitsu.com/dl.aspx?id=d4ebd846-aa0c-478b-8f58-4cfbf3230473">http://docs.ts.fujitsu.com/dl.aspx?id=d4ebd846-aa0c-478b-8f58-4cfbf3230473</a>
<b>Operating system notes</b>	Support of other Linux derivatives on demand Red Hat® certification starting with version 5.8 / 6.4.

**Server Management**

<b>Standard</b>	ServerView Remote Management (iRMC)
<b>Option</b>	ServerView Suite - Maintain iRMC Advanced Pack incl. Advanced Video Redirection (AVR), video capturing and Virtual Media ServerView Suite - Dynamize Virtual-IO Manager (VIOM) Resource Orchestrator Virtual Edition (ROR VE) Resource Orchestrator Cloud Edition (ROR CE) ServerView Suite - Integrate Integration pack for Fujitsu ManageNow® solution
<b>Server Management notes</b>	Regarding dependencies for ServerView Suite software products see dedicated product data sheets.

**Dimensions / Weight**

<b>Floor-stand (W x D x H)</b>	98 x 399 x 340 mm
<b>Dimension notes</b>	without feet
<b>Weight</b>	up to 10 kg
<b>Weight notes</b>	Actual weight may vary depending on configuration

**Environmental**

<b>Operating ambient temperature</b>	10 - 35 °C
<b>Operating relative humidity</b>	10 - 85 % (non condensing)
<b>Operating environment</b>	FTS 04230 – Guideline for Data Center (installation specification)
<b>Operating environment link</b>	<a href="http://docs.ts.fujitsu.com/dl.aspx?id=e4813edf-4a27-461a-8184-983092c12dbe">http://docs.ts.fujitsu.com/dl.aspx?id=e4813edf-4a27-461a-8184-983092c12dbe</a>
<b>Sound pressure (LpAm)</b>	SATA: 22 dB(A) idle mode / 23 dB(A) operating mode; SAS: 33 dB(A) idle mode / 35 dB(A) operating mode
<b>Sound power (LWAd; 1B = 10dB)</b>	SATA: 3.7 B idle mode / 3.7 B operating mode; SAS: 4.9 B idle mode/ 5 B operating mode
<b>Noise notes</b>	Noise emissions and operation modes depend on system configuration.

**Electrical values**

<b>Power supply configuration</b>	1x standard power supply - with 0-Watt functionality
<b>Standard power supply output</b>	250 W (94 % efficiency, 80 PLUS platinum)
<b>Rated voltage range</b>	100 V - 240 V
<b>Rated frequency range</b>	47 Hz - 63 Hz
<b>Rated current max.</b>	100V-240V/6A-3A
<b>Rated current in basic configuration</b>	100V-240V/0.25A-0.22A
<b>Active power (min. configuration)</b>	25 W
<b>Active power (max. configuration)</b>	147 W
<b>Active power note</b>	To estimate the power consumption of different configurations use the Power Calculator of the System Architect: <a href="http://configurator.ts.fujitsu.com/public/">http://configurator.ts.fujitsu.com/public/</a>
<b>Apparent power (max. configuration)</b>	152 VA
<b>Heat emission</b>	529.2 kJ/h (501.6 BTU/h)

**Compliance**

<b>Global</b>	CB RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment)
<b>Germany</b>	GS
<b>Europe</b>	CE Class A *
<b>USA/Canada</b>	CSA us ULc/us FCC Class A
<b>South Korea</b>	KC
<b>China</b>	CCC
<b>Compliance link</b>	<a href="http://globalsp.ts.fujitsu.com/sites/certificates">http://globalsp.ts.fujitsu.com/sites/certificates</a>
<b>Compliance notes</b>	Above mentioned compliances are planned but not available at preliminary stage. There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request. * Warning: This is a class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.

# Components

## Storage drives

SSD SATA, 6 Gb/s, 800 GB, Mainstream Endurance, hot-plug, 2.5-inch, enterprise
SSD SATA, 6 Gb/s, 400 GB, Mainstream Endurance, hot-plug, 2.5-inch, enterprise
SSD SATA, 6 Gb/s, 200 GB, Mainstream Endurance, hot-plug, 2.5-inch, enterprise
SSD SATA, 6 Gb/s, 100 GB, MLC, hot-plug, 2.5-inch, enterprise
SSD SATA, 6 Gb/s, 100 GB, Mainstream Endurance, hot-plug, 2.5-inch, enterprise
HDD SATA, 6 Gb/s, 500 GB, 7,200 rpm, non hot plug, 3.5-inch, economic
HDD SATA, 6 Gb/s, 500 GB, 7,200 rpm, non hot plug, 3.5-inch, business critical
HDD SATA, 6 Gb/s, 500 GB, 7,200 rpm, hot-plug, 2.5-inch, business critical
HDD SATA, 6 Gb/s, 250 GB, 7,200 rpm, non hot plug, 3.5-inch, economic
HDD SATA, 6 Gb/s, 250 GB, 7,200 rpm, hot-plug, 2.5-inch, business critical
HDD SATA, 6 Gb/s, 3 TB, 7,200 rpm, non hot plug, 3.5-inch, business critical
HDD SATA, 6 Gb/s, 2 TB, 7,200 rpm, non hot plug, 3.5-inch, business critical
HDD SATA, 6 Gb/s, 1 TB, 7,200 rpm, non hot plug, 3.5-inch, business critical
HDD SATA, 6 Gb/s, 1 TB, 7,200 rpm, hot-plug, 2.5-inch, business critical
HDD SAS, 6 Gb/s, 900 GB, 10,000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 600 GB, 15,000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 600 GB, 10,000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 500 GB, 7,200 rpm, hot-plug, 2.5-inch, business critical
HDD SAS, 6 Gb/s, 450 GB, 15,000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 450 GB, 10,000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 300 GB, 15,000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 300 GB, 10,000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 146 GB, 15,000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 1.2 TB, 10,000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 1 TB, 7,200 rpm, hot-plug, 2.5-inch, business critical

## Backup Drives

RDX Drive, 320 GB, 500 GB, 1 TB, 25 MB/s, half height, USB 3.0

## Optical drives

Blu-ray Disc™ Triple Writer, (6x BD-ROM; 8x DVD; 24x CD), slimline, SATA I  
 DVD Super Multi, (8xDVD/DVD+RW, 6xDVD-RW, 5xDVD-RAM; 24xCD/CD-R, 16xCD-RW), slimline, SATA I

## SCSI / SAS Controller

SAS Ctrl. 6 Gbit/s 8 ports ext. PCIe 2.0 x8

## RAID Controller

RAID 5/6 Ctrl., SAS/SATA 6 Gbit/s, Fujitsu RAID Ctrl SAS 6G 5/6 512MB (D2616), 8 ports int.  
 RAID level: 0, 1, 10, 5, 50, 6, 60, 512 MB Cache, Optional BBU for selected systems (based on LSI SAS2108)

RAID 5/6 Ctrl., SAS/SATA 6 Gbit/s, Fujitsu RAID Ctrl SAS 6G 1GB (D3116C), 8 ports int.  
 RAID level: 0, 1, 10, 5, 50, 6, 60, 1 GB, Optional FBU (based on LSI SAS2208)

RAID 5/6 Ctrl., SAS/SATA 6 Gbit/s, Fujitsu RAID Ctrl SAS 6G 1GB (D3116), 8 ports int.  
 RAID level: 0, 1, 10, 5, 50, 6, 60, 1 GB, Optional FBU (based on LSI SAS2208)

RAID 0/1 Ctrl., SAS/SATA 6 Gbit/s, Fujitsu RAID Ctrl SAS 6G 0/1 (D2607), 8 ports int.  
 RAID level: 0, 1, 10, No BBU support

Integrated RAID 0/1 Ctrl., SAS/SATA 3 Gbit/s, 4 ports int.  
 RAID level: 0, 1, 1E, No BBU support (based on LSI 1064e)

## Communication, Network

Ethernet Ctrl. 1 x 1 Gbit/s PCIe 1.1 x1 ( Intel® )  
 Ethernet Ctrl. 2 x 10 Gbit/s PCIe 2.0 x8 ( Fujitsu )  
 Ethernet Ctrl. 2 x 10 Gbit/s PCIe 2.1 x8 ( Intel® )  
 Ethernet Ctrl. 2 x 1 Gbit/s PCIe 2.1 x4 ( Intel® )  
 Ethernet Ctrl. 4 x 1 Gbit/s PCIe 2.1 x4 ( Intel® )

## Graphics

NVIDIA® Quadro® NVS 300 LP, PCIe x1, 2x DVI/VGA

---

**Warranty**

**Standard Warranty** 1 year

**Service level** Onsite Service

**Warranty Terms & Conditions** <http://support.ts.fujitsu.com/warranty/Index.asp?LNG=COM>

**Maintenance and Support Services - the perfect extension**

**Support Pack Options** Globally available in major business areas:  
9x5, Next Business Day Onsite Response Time  
9x5, 4h Onsite Response Time  
24x7, 4h Onsite Response Time

**Recommended Service** 24x7, Onsite Response Time: 4h - For locations outside of EMEA please contact your local Fujitsu partner.

**Service Lifecycle** 5 years after end of product life

**Service Weblink** <http://www.fujitsu.com/fts/services/support>

# More information

## Fujitsu OPTIMIZATION Services

In addition to Fujitsu PRIMERGY TX120 S3p, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

### Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

### Computing Products

[www.fujitsu.com/global/services/computing/](http://www.fujitsu.com/global/services/computing/)

### Software

[www.fujitsu.com/software/](http://www.fujitsu.com/software/)

## More information

Learn more about Fujitsu PRIMERGY TX120 S3p, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.  
[www.fujitsu.com/fts](http://www.fujitsu.com/fts)

## Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



## Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>  
Copyright © Fujitsu Technology Solutions

## Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

**Contact**  
FUJITSU LIMITED

Website: [www.fujitsu.com](http://www.fujitsu.com)  
2014-10-08 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>  
Copyright © Fujitsu Technology Solutions